

EazyTalk - GSM Talkback System

- Auto calling to emergency numbers on pressing panic switch
- 5 Emergency & Admin numbers can be stored
- SMS based configuration by admin numbers
- Independent reserved audio channel for playing any external audio



Technical Specifications

	Parameters	Specifications
Power Supply	Rated Voltage	12V DC / 1 A (10% Tolerance)
	Nominal Current	500 mA
Communication	Mode	GPRS [4G Communication with 2G fallback)
	Sim Card	Micro Sim Card
	GSM Frequency	2300 MHz (TD-LTE), 1800 MHz (FDD-LTE), and 850 MHz (FDD-LTE)
Functional Characteristics	Mobile Number Storage	Emergency Numbers – 5 Admin Numbers - 5
	Configuration	SMS-based configuration
	Security	1. Whitelisting of Admin numbers for configuration 2. Call blocking – Only emergency numbers can call
	Fail-Safe protection	1. Watchdog available 2. Network reset on SIM detection
	Zones	Panic switch zone
	Dial Features	1. Auto-calling and SMS to stored numbers in round robin fashion when panic switch is pressed 2. User can independently call for two-way communication
	Audio Features	One mic and speaker for two-way communication
Environmental Parameters	Operating Temperature	0°C to 55°C
	Humidity	95% RH
	Environment	Residential / Commercial / Light Industrial
Mechanical	Material	Sheet metal
	Colour	Gray
	Mounting Type	Screw mounting
	Dimensions	168 x 110 x 29 mm
	Weight	401 g (without packaging)

▪ Dimensions (All dimensions are in mm)

